

Surface Mounted Underwater Yacht Lighting

AL UWL303 SM




BOAT SIZE : 15-100 mt. / 50-330 ft.


- The resistant toward salt water thanks to Aluminium Bronze body
- The High-Tech Power Led has high watt. Every Led is 5 Watt
- Every LED has 140-160Lumen
- RGBW full colour LED
- 12 mm Shockproof Tempered Glass
- 2x1,5 mm² Neopren RNF cable.
- Body assembly is practical. 20 mm cable hole is drilled on the surface of the hull and the surface of the boat is mounted underwater.




Product Specifications









Product Code	AL UWL303 SM
Boat Dimensions mt./ft.	15mt 100mt. / 50ft 330ft.
Single Colour LED	White 64x5W & Royal Blue 64x3W 3535 High Power LED / LED Degree 110°
RGBW Led	60x5W 3535 High Power LED / LED Degree 110°
Volt	DC10V-30V
Current	11.0A - 22.0A
Watt	Single Colour 256W RGBW 240W.
LED Colour / Lumen	White 36000 lumen , Royal Blue 13440 lumen
RGBW Colour / Lumen	R: 3000 lumen, G: 7200 lumen, B: 1800 lumen, W: 9000 lumen, RGBW: 21000 lumen
IP Code	IP68 CLASS III
Body Material	Marine Aluminum Bronze Body, AISI 316L Stainless Steel Back Cover
Glass	12 mm. Special Tempered Glass
Product Cable	Single Colour 2 mt. 2x2,5 RNF Marine Cable , RGBW 2 mt. 5x1 RNF Marine Cable
Driver	External Constant Current Led Driver
Underwater Camera	Not applicable.
Product Sizes	Light Head Diameter: 158mm. , Head Height: 23mm. , Full Length: 68mm. , Glass Diameter: 81mm.
Hole Diameter	20 mm.
Weight	2,350 gr.



/I Do not use in waterless environment.