AL 4051

PAR38 LIGHTING



Garden Lighting › Stake & Stand Mounted LED Lighting

The AL 4051 is a PAR38 garden floodlight from the stake and surface mounted range, suitable for lighting trees, walls and façades. It is made with an N6 body resistant to heat and impact and a silicone gasket, giving IP65 protection. The fitting takes a PAR38 - 80W lamp in an E27 socket, runs at 220 V and is finished in matt black.

PROTECTION RATING **IP65**	OPERATING VOLTAGE **220 V**	POWER **80 W**
ELECTRICAL CLASS **Class II**	WARRANTY **1-year warranty**	

BODY COLOUR	Matt black
POWER	80 W
OPERATING VOLTAGE	220 V

Important Bulb not included.

CERTIFICATES AND PROPERTIES

IP65 · UV resistant · Recyclable · CE · 1 year warranty · Class II · Suitable for direct mounting on normally flammable surfaces · Dust-tight · Protected against water jets

FEATURES

Specifications

- Resistant to heat and impact
- N6 body
- Silicone gasket

TECHNICAL DATA

LIGHT

Bulb	PAR38 - 80W


BODY AND MOUNTING

Colour	Matt Black

ELECTRICAL

Socket	E27
Volt	220 V

DIMENSION DRAWINGS



Dimensions in millimetres (catalogue 2027).

PRODUCT CODES

Code	Body colour	Power
AL 4051 (PAR38)	—	80 W

AK BORU ELK. MALZ. LTD. ŞTİ. · **AKER LIGHTING**
Office: Perpa Ticaret Merkezi A Blok Kat 8 No:702, 34384 Okmeydanı – Şişli / İstanbul
Tel: +90 212 210 25 26

AKBORU
www.akboru.com
info@akboru.com